

TECHNICAL DATA – ENGINE »

ENGINE	50 AC SENIOR ADVENTURE	50 AC MINI ADVENTURE
Design	single cylinder 2-stroke engine, with reed valve inlet	
Displacement	49.0 ccm	
Bore/Stroke	39.5 / 40 mm	
Fuel	Lead-free SUPER FUEL (RON 95), mixed with 2-stroke oil	Lead-free SUPER FUEL (RON 95)
Lubrication	mixture lubrication	separate lubrication
Oil/gasoline ratio	1 : 60	–
2-stroke oil	high-grade two-stroke oils for mixture lubrication (Motorex Cross Power 2T)	high-grade two-stroke oils for separate lubrication (Motorex Cross Power 2T)
Crankshaft bearing	2 grooved ball bearing	
Connecting rod bearing	needle bearing	
Piston pin bearing	needle bearing	
Piston rings	1 rectangular ring	
Primary drive	straight cut spur gears, 16 : 57 t	
Transmission oil	0.15-0.2 liter (0.033-0.044 US gal) gear oil Dexron II (Motorex ATF Super)	
Spark plug	NGK BR 8 ECM	
Electrode gap	0.6 mm (0.0236 in)	
Carburetor	Dell'Orto PHVA 14 DS	Dell'Orto PHVA 12 XS
Airfilter	wet foam type air filter insert	

BASIC CARBURETOR SETTING		
MODEL	50 SENIOR ADVENTURE	50 MINI ADVENTURE
Type	Dell'Orto PHVA 14 DS	Dell'Orto PHVA 12 XS
Main jet	80 (70)	65 (70)
Needle jet	211 FA	211 FA
Idling jet	45	38
Jet needle	A10	A10
Needle position from top	3 rd	4 th
Air/Mixture reg. screw open	3.5	4
Slide	40	40
Starting jet	60	60

TIGHTENING TORQUES – ENGINE		
Primary gear nut	M14x1.25	40 Nm
Hexagon nut ignition rotor	M10x1.25	20 Nm
Nut of clutch hub	M10x1.25	Loctite 243 + 35 Nm
Cylinder head screws	M7	15 Nm
Cylinder base nuts	M8	18 Nm
Allen head bolt - Stator	M5x25	Loctite 243 + 8 Nm
Oil plug	M16	5 Nm
Oil drain plug	M10	15 Nm
Other engine bolts	M5	7 Nm
	M6	10 Nm
	M8	30 Nm