

KTM
Freigabe

Ereignisfeld



The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!

This legend shall be included on any kind of reproduction of this document.

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!

Dieser Text muss auf jeder Reproduktion dieses Dokumentes aufscheinen.

Article number:	12.18.7D.01	Type:	5018 PDS DCC				
MOVEX - description:	KTM 125 SX'08	Compression damping valve:	DCC 10 cpl. XC '07 5018.0213S10				
		Driving comfort	STANDARD	Driving sport	max. payload		
Compression damping Low Speed (clicks open or marking)		16	14	12			
Compression damping High Speed (turns open)		2	1	3/4			
Rebound damping (clicks open or marking)		25	23	22			
Spring preload		mm	5 mm	mm	mm		
Preload Adjuster (turns preload)							
Static sag		33 mm		Needle			
Riding sag		107 mm		Rebound disk height			
Gas pressure		10 bar		Stroke			
Oil type		5018.0342		Shock length			
Oil viscosity		SAE 2.5					
Spring	Riders weight	Spring rate	Spring description	Spring length	Part number		
Spring softer	65-75 kg	57 N/mm	(62) 57-250	250 mm	9121.0071		
Spring STANDARD	75-85 kg	60 N/mm	(62) 60-250	250 mm	9121.0055		
Spring harder	85-95 kg	63 N/mm	(62) 63-250	250 mm	9121.0053		
Shims piston 1				Shims piston 2			
Qty	Compression	Qty	Rebound	Qty	Compression	Qty	Rebound
1	Ø 16x21x0.30	1	Ø 16x20x0.30	1	Ø 16x20x0.30	1	Ø 16x22x0.30
1	Ø 16x30x0.20	1	Ø 16x28x0.30	2	Ø 16x34x0.20	1	Ø 16x30x0.25
1	Ø 16x32x0.20	1	Ø 16x30x0.25	2	Ø 16x36x0.20	2	Ø 16x36x0.25
1	Ø 16x34x0.20	1	Ø 16x32x0.15	2	Ø 16x38x0.20		
1	Ø 16x36x0.20	1	Ø 16x32x0.20	2	Ø 16x40x0.20		
1	Ø 16x38x0.20	1	Ø 16x34x0.20				
1	Ø 16x40x0.20	1	Ø 16x26x0.15				
1	Ø 16x42x0.20	2	Ø 16x36x0.20				
3	Ø 16x44x0.15						
1	Ø 16x36x0.15						
5	Ø 16x44x0.25						
Piston number	5018-0197			Piston number	5018-0446		
Piston bleed	no			Piston bleed	0 mm		
Details compression unit:				Legend:		TBD = to be defined - = no comment	
Qty	Description, dimension	Note:					
1	Adjusting spring DCC C16						
1	Backpl. Ø6x9,5x0,30						
1	Shim Ø6x14x0,25						
1	Shim Ø6x16x0,25						
1	Shim Ø6x18x0,25						
2	Shim Ø6x20x0,25						
1	Shim Ø6x22x0,15						
1	Shim Ø6x14x0,10						
1	Shim Ø6x22x0,25						
C	2007-03-01	Rauscher	Feld ausfüllen (Englisch)!!	Draftsman:	Rauscher A.		
B	2007-02-19	Rauscher	Feld ausfüllen (Englisch)!!	Creation date:	2006-12-13		
A	2006-12-21	Rauscher	Feld ausfüllen (Englisch)!!				
Index	Date	Name	Modification description				
Total number of release documents		1					