

250 EXC-F 08	Conditions:	STANDARD
	Sea Level [m] :	300 - 1500m
	Temperature [°C] :	10 - 25
	Carburetor : KEIHIN FCR - MX 3900	
	Exhaust system	STANDARD & AKRAPOVIC
	Idler Jet:	42
	Idle Mixture Screw:	1.5 Revolutions open
	Main Jet:	168
	Needle:	OBETP 5. Position from top
	Accelerator Pump:	Leak Jet : 70 Pump Spring: GREEN (KTM Nr.: SXS08250030)

HOT	COLD
300 - 1500m	300 - 1500m
30 ++	-5 - +5
STANDARD & AKRAPOVIC	STANDARD & AKRAPOVIC
42	42
1.25 Revolutions open	1.75 Revolutions open
168	175 (KTM Nr.: 545.31.623.175)
OBETP 4. Position from top	OBETP 6. Position from top
Leak Jet : 70	Leak Jet : 70
Pump Spring: GREEN (KTM Nr.: SXS08250030)	Pump Spring: GREEN (KTM Nr.: SXS08250030)

SAND
0 - 300m
10 - 30
STANDARD & AKRAPOVIC
42
1.75 Revolutions open
175 (KTM Nr.: 545.31.623.175)
OBETP 6. Position from top
Leak Jet : 70
Pump Spring: GREEN (KTM Nr.: SXS08250030)