The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

Settingliste Gabel

Artikelnummer:	05187L19	System:	Open Cartridge
Modellbezeichnung: (ohne Jahresangabe)	KTM 690 Duke Standard	Gabeltyp:	4357

	Fahrer Komfort	STANDARD	Fahrer Sport	volle Nutzlast
Druckstufendämpfung (Klicks offen)	-	-	-	-
Zugstufendämpfung (Klicks offen)	-	-	-	-
Preload Adjuster (im Uhrzeigersinn)	-	-	-	-

Luftkammerlänge STANDARD	- mm
Luftkammerlänge min-max	- mm

Öl Type	4860-1166
Öl Viskosität	SAE 4
Federweg	135 mm
Gabellänge	816 mm

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge mit Vorspannbüchse	Teilenummer
Feder weicher	kg	N/mm		mm	
Feder STANDARD	75-85 kg	6.0 N/mm	6.0-345	350 mm	
Feder härter	kg	N/mm		mm	

Shims Kolben Druckstufe			
Stk	Druckstufe	Stk	Zugstufe
	Ø		Ø
1	Ø 14x33x0.40		
Wechselventil Hubhöhe			2,5, pre-load 5mm
Wechselventil Feder Nummer			C=1.0
Kolben Nummer			
Kolben Freibohrung			0,0 mm

Shims Kolben Zugstufe			
Stk	Druckstufe	Stk	Zugstufe
	Ø		Ø
Wechselventil Hubhöhe			
Wechselventil Feder Nummer			
Kolben Nummer			
Kolben Freibohrung			

Legende:	TBD = to be defined (noch zu definieren)	- = keine Angabe

Bemerkungen:
480ml Öl pro Gabelbein; 15mm pre-load Hauptfeder; Ölstand 10 bis 12mm über Innenrohr (Kolbenstange ganz herausgezogen, Außenrohr nach unten geschoben); WP empfiehlt die Verwendung des spezifizierten Öl-Typs (abweichende Erstbefüllung - India Oil)

Index	Datum	Name	Änderungsbeschreibung

Name Ersteller:	B. Pongratz
Datum Erstellung:	21.02.2012

Freigabefeld

Gesamtseitenanzahl des Freigabedokumentes: 1

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

Front fork setting list

Article number:	05187L19	System:	Open Cartridge
Modeldescription: (without modelyeardeclaration)	KTM 690 Duke Standard	Front fork type:	4357

	Driving comfort	STANDARD	*Driving sport*	*max. payload*
Compression damping (clicks open)	-	-	-	-
Rebound damping (clicks open)	-	-	-	-
Preload Adjuster (clockwise)	-	-	-	-

air chamber length STANDARD	- mm
air chamber length min-max	- mm

Oil type	4860-1166
Oil viscosity	SAE 4
Wheel travel	135 mm
Front fork length	816 mm

Spring	Riders weight	Spring rate	Spring description	Spring length with preload spacer	Part number
Spring softer	*kg*	*N/mm*		*mm*	
Spring STANDARD	75-85 kg	6.0 N/mm	6.0-345	350 mm	
Spring harder	*kg*	*N/mm*		*mm*	

Shims piston compression			
Qty	Compression	Qty	Rebound
	Ø		Ø
1	Ø 14x33x0.40		
Check valve lift height			2,5, pre-load 5mm mm
Check valve spring number			C=1.0
Piston number			
Piston bleed			0 mm

Shims piston rebound			
Qty	Compression	Qty	Rebound
	Ø		Ø
Check valve lift height			
Check valve spring number			
Piston number			
Piston bleed			

Legend:	TBD = to be defined	- = no comment

Note:
480cc oil in each fork leg; 15mm pre-load on main spring; Oil level 10 to 12 mm above Inner-Tube (piston rod fully pulled out, outer tube pulled down); WP recommends the use of the specified oil type (aberrant initial filling - India Oil)

Index	Date	Name	Modification description