The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

SETTINGLIST FORK OEM

Artikelnummer:	**0262C108U406000**	**System:**	**Aerfork**
Modellbezeichnung: (ohne Jahresangabe)	**Husqvarna FS 450 / KTM 450 SMR**	**Gabeltyp:**	XACT 5448

	Fahrer Komfort	STANDARD	Fahrer Sport
compression damping (clicks open)	17	12	7
rebound damping (clicks open)	17	12	7

Ölmenge Cartridge rechts	380	ml
Fettmenge Cartridge links	5	g
Ölmenge Außenwerk rechts	200	ml
Ölmenge Außenwerk links	200	ml

min/max	180/240	ml
min/max	180/240	ml

Öl Type	48601166
Öl Viskosität	SAE 4
Federweg	278mm
Gabellänge	920mm

Einstellung	Gewicht Fahrer	Luftdruck
Weicher	65-75 kg	10,2 bar
STANDARD	75-85 kg	10,4 bar
Härter	85-95 kg	10,6 bar

Shims Kolben Midvalve

Stk	Druckstufe	Stk	Zugstufe
2	8x12x0,25	1	6x18x4
8	8x24x0,15	3	6x10x0,15
2	8x20x0,15	1	6x12x0,15
1	8x16x0,15	1	6x16x0,15
1	8x12x0,10	1	6x18x0,15
1	8x14x0,15	1	6x20x0,15
1	8x16x0,15	1	6x22x0,15
1	8x18x0,15	1	6x24x0,15
1	8x20x0,15	1	6x26x0,10
1	8x22x0,10	2	6x28x0,15
2	8x24x0,10		
3	8x26x0,10		
4	8x28x0,10		
8	8x30x0,10		
2	6x9x0,20		

Wechselventil Hubhöhe	-mm
Kolben Midvalve Art.Nr.	48602139S

Shims Kolben Basevalve

Stk	Druckstufe	Stk	Zugstufe
1	6x25x4	1	6x18x4
1	6x16x0,10	1	6x10x0,20
1	6x20x0,10	1	48601841
1	6x22x0,10		
1	6x24x0,10		
3	6x26x0,10		
5	6x28x0,10		
13	6x30x0,10		

Basevalve Baugruppe Nr.	48602049S2
Kolben Basevalve Art.Nr.	48602005S

Bemerkung

			Ersteller:	Ma.Priewasser
0262C108U406000_-_Serie_SL	Templ.: OEM_AER_Fork_SL_V3	Seite 1/1	**Datum:**	04.10.2019

Husqvarna MOTORCYCLES KTM

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!

SETTINGLIST FORK OEM

Article number:	0262C108U406000	System:	Aerfork
Modeldescription: (without year declaration)	Husqvarna FS 450 / KTM 450 SMR	Type:	XACT 5448

	driving comfort	STANDARD	driving sport
compression damping (clicks open)	17	12	7
rebound damping (clicks open)	17	12	7

oil capacity cartridge right	380	ml
grease quantity cartridge left	5	g
oil capacity outertube right	200	ml
oil capacity outertube left	200	ml

min/max	180/240	ml
min/max	180/240	ml

oil type	48601166
oil viscosity	SAE 4
fork stroke	278 mm
fork length	920 mm

adjustment	riders weight	pressure
softer	65-75 kg	10,2 bar
STANDARD	75-85 kg	10,4 bar
harder	85-95 kg	10,6 bar

Shims Piston Midvalve

Qty	Compression	Qty	Rebound
2	8x12x0,25	1	6x18x4
8	8x24x0,15	3	6x10x0,15
2	8x20x0,15	1	6x12x0,15
1	8x16x0,15	1	6x16x0,15
1	8x12x0,10	1	6x18x0,15
1	8x14x0,15	1	6x20x0,15
1	8x16x0,15	1	6x22x0,15
1	8x18x0,15	1	6x24x0,15
1	8x20x0,15	1	6x26x0,10
1	8x22x0,10	2	6x28x0,15
2	8x24x0,10		
3	8x26x0,10		
4	8x28x0,10		
8	8x30x0,10		
2	6x9x0,20		

check valve lift height	- mm
piston midvalve Art.No.	48602139S

Shims Piston Basevalve

Qty	Compression	Qty	Rebound
1	6x25x4	1	6x18x4
1	6x16x0,10	1	6x10x0,20
1	6x20x0,10	1	48601841
1	6x22x0,10		
1	6x24x0,10		
3	6x26x0,10		
5	6x28x0,10		
13	6x30x0,10		

basevalve assembly nr.	48602049S2
piston basevalve Art.No.	48602005S

Note

			Created by:	Ma.Priewasser
0262C108U406000_-_Serie_SL	Templ.: OEM_AER_Fork_SL_V3	Page 1/1	Creation date:	04.10.2019

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

Husqvarna MOTORCYCLES

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!