The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

SETTINGLIST FORK OEM

Artikelnummer:	**34158U67**	**System:**	**Aerfork**
Modellbezeichnung: (ohne Jahresangabe)	**KTM 350 EXC-F Wess Edition**	**Gabeltyp:**	XACT 5448

	Fahrer Komfort	STANDARD	*Fahrer Sport*
compression damping (clicks open)	*17*	12	7
rebound damping (clicks open)	*23*	18	13

Ölmenge Cartridge rechts	370	ml
Fettmenge Cartridge links	5	g
Ölmenge Außenwerk rechts	230	ml
Ölmenge Außenwerk links	230	ml

min/max	180/240	ml
min/max	180/240	ml

Öl Type	48601166
Öl Viskosität	SAE 4
Federweg	300mm
Gabellänge	940mm

Einstellung	Gewicht Fahrer	Luftdruck
Weicher	*65-75 kg*	*6,8 bar*
STANDARD	75-85 kg	7 bar
Härter	*85-95 kg*	*7,2 bar*

Shims Kolben Midvalve

Stk	Druckstufe	Stk	Zugstufe
7	8x24x0.10	1	6x18x4.00
2	8x14x0.25	1	6x12x0.15
2	8x10x0.15	1	6x16x0.10
1	8x14x0.15	1	6x18x0.10
1	8x16x0.15	1	6x20x0.10
1	8x18x0.15	1	6x22x0.10
1	8x20x0.15	1	6x24x0.10
1	8x22x0.15	1	6x26x0.10
1	8x24x0.15	2	6x28x0.10
1	8x26x0.15	1	6x26x0.10
1	8x28x0.15	1	6x24x0.10
12	8x30x0.10		
1	6x9x0.30		

Wechselventil Hubhöhe	-mm
Kolben Midvalve Art.Nr.	48602139S

Shims Kolben Basevalve

Stk	Druckstufe	Stk	Zugstufe
1	6x25x4.00	1	6x18x4
1	6x12x0.20	1	6x10x0,20
1	6x14x0.15	1	48601841
1	6x16x0.20		
1	6x18x0.15		
1	6x20x0.15		
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
1	6x30x0.15		
1	6x18x0.15		
8	6x30x0.10		

Basevalve Baugruppe Nr.	48602049S2
Kolben Basevalve Art.Nr.	48602005S

Bemerkung

			Ersteller:	S. Schlemmer
34158U67_b_Serie_SL	Templ.: OEM_AER_Fork_SL_V3	Seite 1/1	**Datum:**	14.11.2019

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.

SETTINGLIST FORK OEM

Article number:	34158U67	System:	Aerfork
Modeldescription: (without year declaration)	KTM 350 EXC-F Wess Edition	Type:	XACT 5448

	driving comfort	STANDARD	driving sport
compression damping (clicks open)	17	12	7
rebound damping (clicks open)	23	18	13

oil capacity cartridge right	370	ml
grease quantity cartridge left	5	g
oil capacity outertube right	230	ml
oil capacity outertube left	230	ml

			oil type	48601166
			oil viscosity	SAE 4
min/max	180/240	ml	fork stroke	300 mm
min/max	180/240	ml	fork length	940 mm

adjustment	riders weight	pressure
softer	65-75 kg	6,8 bar
STANDARD	75-85 kg	7 bar
harder	85-95 kg	7,2 bar

Shims Piston Midvalve

Qty	Compression	Qty	Rebound
7	8x24x0.10	1	6x18x4.00
2	8x14x0.25	1	6x12x0.15
2	8x10x0.15	1	6x16x0.10
1	8x14x0.15	1	6x18x0.10
1	8x16x0.15	1	6x20x0.10
1	8x18x0.15	1	6x22x0.10
1	8x20x0.15	1	6x24x0.10
1	8x22x0.15	1	6x26x0.10
1	8x24x0.15	2	6x28x0.10
1	8x26x0.15	1	6x26x0.10
1	8x28x0.15	1	6x24x0.10
12	8x30x0.10		
1	6x9x0.30		

check valve lift height	- mm
piston midvalve Art.No.	48602139S

Shims Piston Basevalve

Qty	Compression	Qty	Rebound
1	6x25x4.00	1	6x18x4
1	6x12x0.20	1	6x10x0,20
1	6x14x0.15	1	48601841
1	6x16x0.20		
1	6x18x0.15		
1	6x20x0.15		
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
1	6x30x0.15		
1	6x18x0.15		
8	6x30x0.10		

basevalve assembly nr.	48602049S2
piston basevalve Art.No.	48602005S

Note

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.