The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!

SETTINGLIST FORK OEM

Artikelnummer:	34188T09	System:	Aerfork
Modellbezeichnung: (ohne Jahresangabe)	KTM 450 SX-F HQV FC 450	Gabeltyp:	XACT 5548

	Fahrer Komfort	STANDARD	Fahrer Sport
compression damping (clicks open)	17	12	7
rebound damping (clicks open)	17	12	7

Ölmenge Cartridge rechts	380	ml
Fettmenge Cartridge links	5	g
Ölmenge Außenwerk rechts	220	ml
Ölmenge Außenwerk links	220	ml

			Öl Type	48601166
			Öl Viskosität	SAE 4
min/max	180/240	ml	Federweg	310mm
min/max	180/240	ml	Gabellänge	950mm

Einstellung	Gewicht Fahrer	Luftdruck
Weicher	65-75 kg	10,5 bar
STANDARD	75-85 kg	10,7 bar
Härter	85-95 kg	10,9 bar

Shims Kolben Midvalve

Stk	Druckstufe	Stk	Zugstufe
1	6x25x4	1	6x25x4
1	6x22x0,15	1	6x10x0,30
1	6x18x0,15	1	6x16x0,10
1	6x12x0,15	1	6x18x0,10
1	6x9x0,10	1	6x20x0,10
2	6x13x0,10	1	6x22x0,10
2	6x16x0,10	1	6x24x0,10
2	6x18x0,10	1	6x26x0,10
2	6x20x0,10	2	6x28x0,10
2	6x22x0,10	2	6x26x0,10
2	6x24x0,10		
2	6x26x0,10		
3	6x28x0,10		
3	6x30x0,10		

Wechselventil Hubhöhe	-mm
Kolben Midvalve Art.Nr.	48602004S

Shims Kolben Basevalve

Stk	Druckstufe	Stk	Zugstufe
1	6x25x4	1	6x18x4
1	6x14x0,15	1	6x10x0.20
1	6x16x0,15	1	48601841
1	6x18x0,15		
1	6x20x0,15		
1	6x22x0,15		
1	6x24x0,15		
1	6x26x0,15		
2	6x28x0,15		
11	6x30x0,15		
2	6x18x0,10		
3	6x30x0,15		

Basevalve Baugruppe Nr.	48602049S
Kolben Basevalve Art.Nr.	48602005S

Bemerkung

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!

SETTINGLIST FORK OEM

Article number:	34188T09	System:	Aerfork
Modeldescription: (without year declaration)	KTM 450 SX-F HQV FC 450	Type:	XACT 5548

	driving comfort	STANDARD	driving sport
compression damping (clicks open)	17	12	7
rebound damping (clicks open)	17	12	7

oil capacity cartridge right	380	ml
grease quantity cartridge left	5	g
oil capacity outertube right	220	ml
oil capacity outertube left	220	ml

			oil type	48601166
			oil viscosity	SAE 4
min/max	180/240	ml	fork stroke	310mm
min/max	180/240	ml	fork length	950mm

adjustment	riders weight	pressure
softer	65-75 kg	10,5 bar
STANDARD	75-85 kg	10,7 bar
harder	85-95 kg	10,9 bar

Shims Piston Midvalve

Qty	Compression	Qty	Rebound
1	6x25x4	1	6x25x4
1	6x22x0,15	1	6x10x0,30
1	6x18x0,15	1	6x16x0,10
1	6x12x0,15	1	6x18x0,10
1	6x9x0,10	1	6x20x0,10
2	6x13x0,10	1	6x22x0,10
2	6x16x0,10	1	6x24x0,10
2	6x18x0,10	1	6x26x0,10
2	6x20x0,10	2	6x28x0,10
2	6x22x0,10	2	6x26x0,10
2	6x24x0,10		
2	6x26x0,10		
3	6x28x0,10		
3	6x30x0,10		

check valve lift height	-mm
piston midvalve Art.No.	48602004S

Shims Piston Basevalve

Qty	Compression	Qty	Rebound
1	6x25x4	1	6x18x4
1	6x14x0,15	1	6x10x0.20
1	6x16x0,15	1	48601841
1	6x18x0,15		
1	6x20x0,15		
1	6x22x0,15		
1	6x24x0,15		
1	6x26x0,15		
2	6x28x0,15		
11	6x30x0,15		
2	6x18x0,10		
3	6x30x0,15		

basevalve assembly nr.	48602049S
piston basevalve Art.No.	48602005S

Note

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.