

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SETTINGLIST FORK OEM

Artikelnummer:	34188U09	System:	Aerfork
Modellbezeichnung: (ohne Jahresangabe)	KTM 450 SX-F	Gabeltyp:	XACT 5448

	<i>Fahrer Komfort</i>	STANDARD	<i>Fahrer Sport</i>
compression damping (clicks open)	17	12	7
rebound damping (clicks open)	17	12	7

Ölmenge Cartridge rechts	380	ml
Fettmenge Cartridge links	5	g
Ölmenge Außenwerk rechts	230	ml
Ölmenge Außenwerk links	230	ml

min/max	180/240 ml	Öl Type	48601166
min/max	180/240 ml	Öl Viskosität	SAE 4
		Federweg	310mm
		Gabellänge	950mm

Einstellung	Gewicht Fahrer	Luftdruck
<i>Weicher</i>	65-75 kg	10,5 bar
STANDARD	75-85 kg	10,7 bar
<i>Härter</i>	85-95 kg	10,9 bar

Shims Kolben Midvalve			
Stk	Druckstufe	Stk	Zugstufe
2	8x12x0,25	1	6x25x4
2	8x24x0,15	1	6x10x0,30
2	8x20x0,10	1	6x16x0,10
3	8x18x0,10	1	6x18x0,10
3	8x16x0,10	1	6x20x0,10
2	8x14x0,10	1	6x22x0,10
2	8x12x0,10	1	6x24x0,10
1	8x10x0,20	1	6x26x0,10
1	8x11x0,10	2	6x28x0,10
2	8x12x0,10	2	6x26x0,10
3	8x15x0,10		
3	8x20x0,10		
3	8x22x0,10		
3	8x24x0,10		
2	8x26x0,15		
3	8x28x0,15		
8	8x30x0,15		
1	6x8x0,30		
1	6x9x0,15		
4	6x9x0,30		
Wechselventil Hubhöhe		-mm	
Kolben Midvalve Art.Nr.		486021395	

Shims Kolben Basevalve			
Stk	Druckstufe	Stk	Zugstufe
1	6x25x4	1	6x18x4
1	6x14x0,15	1	6x10x0,20
1	6x16x0,15	1	48601841
1	6x18x0,15		
1	6x20x0,15		
1	6x22x0,15		
1	6x24x0,15		
1	6x26x0,15		
2	6x28x0,15		
11	6x30x0,15		
2	6x18x0,10		
3	6x30x0,15		
Basevalve Baugruppe Nr.		48602049S2	
Kolben Basevalve Art.Nr.		48602005S	

Bemerkung

SETTINGLIST FORK

OEM

Article number:	34188U09	System:	Aerfork
Modeldescription: (without year declaration)	KTM 450 SX-F	Type:	XACT 5448

	<i>driving comfort</i>	STANDARD	<i>driving sport</i>
compression damping (clicks open)	<i>17</i>	12	7
rebound damping (clicks open)	<i>17</i>	12	7

oil capacity cartridge right	380	ml
grease quantity cartridge left	5	g
oil capacity outertube right	230	ml
oil capacity outertube left	230	ml

oil type	48601166
oil viscosity	SAE 4
min/max	180/240 ml
fork stroke	310 mm
min/max	180/240 ml
fork length	950 mm

adjustment	riders weight	pressure
<i>softer</i>	<i>65-75 kg</i>	<i>10,5 bar</i>
STANDARD	75-85 kg	10,7 bar
<i>harder</i>	<i>85-95 kg</i>	<i>10,9 bar</i>

Shims Piston Midvalve			
Qty	Compression	Qty	Rebound
2	8x12x0,25	1	6x25x4
2	8x24x0,15	1	6x10x0,30
2	8x20x0,10	1	6x16x0,10
3	8x18x0,10	1	6x18x0,10
3	8x16x0,10	1	6x20x0,10
2	8x14x0,10	1	6x22x0,10
2	8x12x0,10	1	6x24x0,10
1	8x10x0,20	1	6x26x0,10
1	8x11x0,10	2	6x28x0,10
2	8x12x0,10	2	6x26x0,10
3	8x15x0,10		
3	8x20x0,10		
3	8x22x0,10		
3	8x24x0,10		
2	8x26x0,15		
3	8x28x0,15		
8	8x30x0,15		
1	6x8x0,30		
1	6x9x0,15		
4	6x9x0,30		
check valve lift height	- mm		
piston midvalve Art.No.	486021395		

Shims Piston Basevalve			
Qty	Compression	Qty	Rebound
1	6x25x4	1	6x18x4
1	6x14x0,15	1	6x10x0,20
1	6x16x0,15	1	48601841
1	6x18x0,15		
1	6x20x0,15		
1	6x22x0,15		
1	6x24x0,15		
1	6x26x0,15		
2	6x28x0,15		
11	6x30x0,15		
2	6x18x0,10		
3	6x30x0,15		
basevalve assembly nr.	48602049S2		
piston basevalve Art.No.	48602005S		

Note

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration! This legend shall be included on any kind of reproduction of this document.



Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.