

# SETTINGLIST FORK

# OEM

## Modellbezeichnung / Model description

Artikelnummer /  
Article number

A460C103Y406000

KTM 250/300 SX / GG 250/300 MC 2025

	Fahrer Komfort / driving comfort	STANDARD	Fahrer Sport / driving sport
Druckstufendämpfung (Klicks offen) / compression damping (clicks open)	17	12	7
Zugstufendämpfung (Klicks offen) / rebound damping (clicks open)	23	18	13

Ölmenge Cartridge rechts / oil capacity cartridge right	380	ml
Fettmenge Cartridge links / grease quantity cartridge left	5	g
Ölmenge Außenwerk rechts / oil capacity outertube right	240	ml
Ölmenge Außenwerk links / oil capacity outertube left	240	ml

		Öl Viskosität / oil viscosity	SAE 4
min/max	190/250	Federweg / fork stroke	310 mm
min/max	190/250	Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Luftdruck / pressure
Weicher / softer	65-75 kg 143-165 lb	10 bar
STANDARD	75-85 kg 165-187 lb	10,2 bar
Härter / harder	85-95 kg 187-209 lb	10,4 bar

Shims Kolben Midvalve / shims piston midvalve			
Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
3	8x12x0.20	1	6x18x4
1	8x24x0.20	4	6x18x0.40
1	8x20x0.20	1	6x10x0.15
1	8x16x0.20	1	6x11x0.15
1	8x12x0.20	1	6x16x0.10
1	8x11x0.20	1	6x18x0.10
2	8x12x0.10	1	6x20x0.10
1	8x13x0.15	1	6x22x0.10
1	8x14x0.15	1	6x24x0.10
1	8x16x0.15	1	6x26x0.10
1	8x18x0.15	2	6x28x0.10
1	8x20x0.15	1	6x26x0.10
1	8x22x0.15	1	6x24x0.10
1	8x24x0.15		
1	8x26x0.15		
2	8x28x0.15		
6	8x30x0.15		

Shims Kolben Basevalve / shims piston basevalve			
Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	6x25x4	1	6x18x4
1	6x16x0.20	1	6x10x0.20
1	6x18x0.15	1	48601841
1	6x20x0.15		
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
2	6x30x0.15		
1	6x21x0.10		
10	6x30x0.15		

Basevalve Baugruppe Nr.: / basevalve assembly no.:	Federrate & -länge / spring rate & length	16 N/mm
48602049s5		114 mm