

SETTINGLIST FORK

OEM

Modellbezeichnung / Model description

Artikelnummer /
Article number

A460C105Y406000

KTM 250 SX-F / GG 250 MCF 2025 EU

	Fahrer Komfort / driving comfort	STANDARD	Fahrer Sport / driving sport
Druckstufendämpfung (Klicks offen) / compression damping (clicks open)	17	12	7
Zugstufendämpfung (Klicks offen) / rebound damping (clicks open)	17	12	7

Ölmenge Cartridge rechts / oil capacity cartridge right	380	ml
Fettmenge Cartridge links / grease quantity cartridge left	5	g
Ölmenge Außenwerk rechts / oil capacity outertube right	240	ml
Ölmenge Außenwerk links / oil capacity outertube left	240	ml

min/max	190/250	ml	Öl Viskosität / oil viscosity	SAE 4
min/max	190/250	ml	Federweg / fork stroke	310 mm
			Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Luftdruck / pressure
Weicher / softer	65-75 kg 143-165 lb	10,1 bar
STANDARD	75-85 kg 165-187 lb	10,3 bar
Härter / harder	85-95 kg 187-209 lb	10,5 bar

Shims Kolben Midvalve / shims piston midvalve			
Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
2	8x12x0,25	1	6x18x4
3	8x24x0,15	3	6x18x0,40
2	8x22x0,15	2	6x9x0,30
1	8x20x0,15	1	6x16x0,10
1	8x18x0,15	1	6x18x0,10
1	8x16x0,15	1	6x20x0,10
1	8x14x0,15	1	6x22x0,10
2	8x12x0,10	1	6x24x0,10
2	8x14x0,10	1	6x26x0,10
1	8x16x0,10	1	6x13x0,10
1	8x18x0,15	3	6x28x0,10
1	8x20x0,15		
1	8x22x0,15		
1	8x24x0,15		
1	8x26x0,15		
2	8x28x0,15		
7	8x30x0,15		
1	6x9x0,15		
1	6x9x0,20		

Shims Kolben Basevalve / shims piston basevalve			
Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	6x25x4	1	6x18x4
1	6x14x0,15	1	6x10x0,20
1	6x16x0,15	1	48601841
1	6x18x0,15		
1	6x20x0,15		
1	6x22x0,15		
1	6x24x0,15		
2	6x26x0,15		
3	6x28x0,15		
2	6x30x0,15		
1	6x22x0,10		
9	6x30x0,15		

Basevalve Baugruppe Nr.: / basevalve assembly no.:	Federrate & -länge / spring rate & length	16 N/mm
48602049s5		114 mm