

TECHNICAL SPECIFIKATIONS - CASSIS

	250/300 SX	300 MXC	250/300 EXC	250/300 E-GS
Frame	Central chrome-moly-steel frame			
fork	White Power Up Side Down Multiadjuster 4054			
Wheel travel front/rear	300/320 mm			
Rear suspension	Central shock absorber with PRO-LEVER-linkage to rear swing-arm with needle bearing			
Front brake	Disc brake with carbon-steel brake disc Ø 260mm, brake caliper floated			
Rear brake	Disc brake with carbon-steel brake disc Ø 220mm, brake caliper floated			
Tyres front	80/100-21, 90/90-21	90/90-21	90/90-21	90/90-21
Tyres rear	110/90-19, 120/80-19	120/90-18	120/90-18, 4.50-18	120/80-18, 140/80-18
Fuel tank capacity	9 Liter	9 oder 13 Liter	9 oder 13 Liter	9 oder 13 Liter
Final drive ratio	14:50 Z	14:52 Z	14:50Z, 14:52Z	14:50Z, 15:48Z
Chain	5/8 x 1/4"			
Steering angle	62,5°			
Wheel base	1480 ± 10 mm			
Seat high	945 mm			
Ground clearance	385 mm			
Dead-weight without fuel	99,5 kg / 219,6 lbs	100 kg / 220,7 lbs	108 kg / 238,3 lbs	112 kg / 246,4 lbs
Max. permissible front axle load		110 kg / 242 lbs	110 kg / 242 lbs	110 kg / 242 lbs
Max. permissible rear axle load		220 kg / 484 lbs	220 kg / 484 lbs	220 kg / 484 lbs
Max. permissible laden weight		310 kg / 682 lbs	310 kg / 682 lbs	310 kg / 682 lbs