

125/250/300SIXDAYS2006

ERGÄNZUNG ART. NR. 3.211.112

ZUR BEDIENUNGSANLEITUNG ART. NR. 3.211.72

SUPPLEMENT ART. NO. 3.211.112

TO OWNER'S MANUAL ART. NR. 3.211.72



KTM Group Partner

KTM Sportmotorcycle AG
A-5230 Mattighofen
www.ktm.at

TECHNISCHE DATEN - FAHRGESTELL / TECHNICAL DATA - CHASSIS »

STANDARD-EINSTELLUNG – GABEL / STANDARD ADJUSTMENT – FORK			
	125 EXC SIX DAYS	250 EXC SIX DAYS	300 EXC SIX DAYS
	WP 4860 MA-PA 14.18.7B.27	WP 4860 MA-PA 14.18.7B.28	WP 4860 MA-PA 14.18.7B.01
Druckstufendämpfung / Compression adjuster	20	20	18
Zugstufendämpfung / Rebound adjuster	20	20	20
Feder / Spring	4,0 N/mm	4,2 N/mm	4,2 N/mm
Federvorspannung / Spring preload	3 mm	3 mm	5 mm
Luftkammerlänge / Air chamber length	110 mm	110 mm	100 mm
Gabelöl / Fork oil	0401 Motorex	0401 Motorex	0401 Motorex

STANDARD-EINSTELLUNG – FEDERBEIN / STANDARD ADJUSTMENT – SHOCK ABSORBER		
	125 EXC SIX DAYS	250/300 EXC SIX DAYS
	WP PDS 5018 DCC 12.18.7B.24	WP PDS 5018 DCC 12.18.7B.25
Druckstufendämpfung / Compression adjuster	15 LS (low speed) 1,5 HS (high speed)	15 LS (low speed) 1,5 HS (high speed)
Zugstufendämpfung / Rebound adjuster	22	22
Feder / Spring	72/250	76/250
Federvorspannung / Spring preload	5 mm	5 mm