

# JETTING LIST MY 2009 : 250 SX-F

Note : Changings compared with STANDARD - jetting **FAT** - printed !!!

conditions :	STANDARD	HOT	COLD
over sea-level [m] :	300 - 1500	300 - 1500	300 - 1500
temperature [°C] :	10 - 25	25 - 30 ++	-5 - +5
carburetor : KEIHIN FCR - MX 3925			
exhaust-system	STANDARD & AKRAPOVIC	STANDARD & AKRAPOVIC	STANDARD & AKRAPOVIC
idle jet :	40	40	40
idle mixture regulation screw :	1.25 turns open	1.0 turns open	1.5 turns open
main jet :	175	<b>170 (KTM no.: 545.31.623.170)</b>	175
jet needle :	OBEKP 4. position from top	OBEKP 3. position from top	OBEKP 4. position from top
acceleration - pump :	leak jet : 50 pump spring : GREEN	leak jet : 50 pump spring : GREEN	leak jet : 50 pump spring : GREEN

conditions :	SAND	SEALEVEL
over sea-level [m] :	0 - 300	300 - 1500
temperature [°C] :	10 - 30	10 - 25
carburetor : KEIHIN FCR - MX 3925		
exhaust-system	STANDARD & AKRAPOVIC	STANDARD pipe + EXC-F muffler
idle jet :	40	40
idle mixture regulation screw :	1.25 turns open	1.75 turns open
main jet :	<b>180 (KTM no.: 545.31.623.180)</b>	175
jet needle :	OBEKP 3. position from top	OBEKP 3. position from top
acceleration - pump :	leak jet : 50 pump spring : GREEN	leak jet : 50 pump spring : GREEN