

TECHNICAL SPECIFICATIONS – CHASSIS »

CHASSIS	640 DUKE II
Frame	Central chrome-moly-steel frame
Fork	typeWP 4357 MXMA 05187B03 wheel travel140 mm (5.5 in) standard adjustment compressiondriver only = 14, with passenger = 14 standard adjustment rebounddriver only = 16, with passenger = 16 fork leg projection upper fork bridge ...3 mm (0.12 in) oil capacity per fork legappr. 400 ccm (24 cubic in) / SAE 5 air chamber lenght100 mm (4 in)
Rear suspension	WP central shock absorber with PRO-LEVER linkage to rear- swing-arm with needle bearing
Shock absorber	typeWP central shock absorber BAVP 4681 01187B05 rear wheel travel170 mm (6.7 in) standard adjustment compressiondriver only = 3, with passenger = 5 standard adjustment rebounddriver only = 5, with passenger = 6 spring preloaddriver only = 18 mm (0.7 in), with passenger = 23 mm (0.9 in) spring type80 - 260
Front brake	Disc brake with carbon-steel floated brake disc Ø 320 mm (12.6 in) and 4-piston brake caliper
Rear brake	Disc brake with carbon-steel brake disc Ø 220 mm (8.7 in) and single-piston brake caliper floated
Tyres	front: 120/70 R 17 58H - MTR 01 rear: 160/60 R 17 69H - MTR 02
Air pressure rider only	2.0 bar (29 psi) 2.2 bar (32 psi)
Air pressure with passenger	2.2 bar (32 psi) 2.4 bar (35 psi)
Fuel tank capacity	11.2 liters (2.96 US gallons), out of this 2.5 liters (0.62 US gallons) reserve
Final drive ratio	17 : 42
Chain	X-ring 5/8 x 1/4"
Lamps	low beamHB3 12V 60W (socket P20d) high beamHB3 12V 60W (socket P20d) parking light12V 5W (socket W2,1x9,5d) speedometer, tachometer light12V 1,7W (socket W2x4,6d) indicator lamp12V 1,2W (socket W2x4,6d) stop and taillight12V 21/5W (socket BaY15d) flasher12V 10W (socket Ba15s)
Battery	maintenance-free battery 12V 8Ah
Steering angle	63.5°
Wheel base	1460 ± 15 mm (57.5 ± 0.6 in)
Seat high	900 mm (35.5 in)
Ground clearance	280 mm (11 in)
Dead weight without fuel	148 kg (327 lbs)
Max. permissible front axle load	150 kg (331 lbs)
Max. permissible rear axle load	200 kg (441 lbs)
Max. permissible laden weight	350 kg (773 lbs)

TECHNICAL SPECIFICATIONS – CHASSIS »

TIGHTENING TORQUES – CHASSIS 640 DUKE II			
Front axle	M17		40 Nm
Rear axle	M20x1,5		80 Nm
Shock absorber bolts top	M10		45 Nm
Shock absorber bolts bottom	M10		45 Nm
Collar screws brake disk front / rear	M8 / M6 10.9	Loctite 243 +	14 Nm
Bolts brake caliper front	M10x1,25	Loctite 243 +	45 Nm
Allen head bolts brake caliper support rear	M10		40 Nm
Bearing bolt linkage arm/frame	M12x1,75		60 Nm
Collar nuts rocker arm bolts	M14x1,5		100 Nm
Engine mounting screw	M10		45 Nm
Ball joint for push rod	M8	Loctite 243 +	25 Nm
Sprocket bolts with nuts	M8	Loctite 243 +	35 Nm
Collar nut swing arm bolt	M14x1,5		100 Nm
Clamp bolts for top triple clamp	M8		15 Nm
Clamp bolts for bottom triple clamp	M8		15 Nm
Clamp bolts for fork stubs	M8		15 Nm
Collar nut for eccentric chain adjuster	M10		40 Nm
Bolts, handlebar clamp	M8	Loctite 243 +	20 Nm
Allen head bolts handlebar support	M10	Loctite 243 +	20 Nm
Bleeder screw oil reservoir frame	M16x1,5		25 Nm
Other screws on chassis	M6		10 Nm
	M8		25 Nm
	M10		45 Nm
Other collar nuts on chassis	M6		15 Nm
	M8		30 Nm
	M10		50 Nm