Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SHOCK SETTING LIST
MOTORSPORTS

PERFORMANCE SYSTEMS

Artikelnummer:	**15180O02**	**Typ:**	**4618**
Modellbezeichnung: (ohne Jahresangabe)	**KTM RC 125 - 390**	**Druckstufen-ventil**	**DCC 50180213S23**

	Fahrer - Komfort	STANDARD	*Fahrer Sport*	*volle Nutzlast*
Druckstufendämpfung Low Speed (Klicks offen bzw.Markierung)		14		
Druckstufendämpfung High Speed (Umdrehungen offen)		1.5		
Zugstufendämpfung (Klicks offen bzw. Markierung)		14		
Federvorspannung		8 mm		
Trax Hub		x		

Statischer Durchhang	
Fahrtdurchhang	
Gasdruck	10 bar
Öltype	50180751
Öl Viskosität	

Trax Feder	x
Höhe Scheibe Zugstufe	4 mm
Hub	58 mm
Einbaulänge	311.5 mm
Gummipuffer	46181171

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge	Teilenummer
Feder weicher	65-75 kg	N/mm	(59) 68-130	mm	70189016
Feder STANDARD	75-85 kg	N/mm	(59) 72-130	mm	70189001
Feder härter	85-95 kg	N/mm	(59) 76-130	mm	70189003

Shims Kolben 1

Stk	Druckstufe	Stk	Zugstufe
1	12x16x0.30	2	12x22x0.30
1	12x26x0.20	1	12x19x0.30
1	12x32x0.20	1	12x22x0.25
1	12x34x0.20	1	12x24x0.25
1	12x36x0.20	1	12x26x0.20
2	12x38x0.25	1	12x28x0.20
3	12x40x0.25	2	12x30x0.20
1	12x36x0.10	1	12x24x0.10
2	12x40x0.25	1	12x32x0.20

Kolben-Nr.:	46810560 mm
Kolben-Freibohrung:	0 mm

Shims Kolben 2

Stk	Druckstufe	Stk	Zugstufe

Kolben-Nr.:	
Kolben-Freibohrung:	

Details Druckstufenventil

Stück	Bezeichnung / Dimension
1	6x9.5x0.30
1	6x14x0.20
1	6x16x0.20
1	6x18x0.20
1	6x20x0.25
4	6x22x0.25

Bemerkungen

Legende

TBD = to be defined (noch zu definieren)

- = keine Angabe

Index	Datum	Name	Änderungsbeschreibung

Name Ersteller:	
Datum Erstellung:	

Freigabefeld

Bitte hier den Dateinamen eingeben | Templ.: MSP_Shock_Setting-list_V01 | Seite 1 / 1

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

SHOCK SETTING LIST
MOTORSPORTS

PERFORMANCE SYSTEMS

Articl-No.:	15180O02	Type:	4618
Model-description: (without year-declaration)	KTM RC 125 - 390	Compression damping valve	DCC 50180213S23

	driving comfort	STANDARD	*driving sport*	*max.payload*
Compression damping Low Speed (clicks or marking)		14		
Compression damping High Speed (turns open)		1.5		
Rebound damping (clicks open or marking)		14		
Spring preload		8 mm		
Trax stroke		x		

Static sag	
Riding sag	
Gas pressure	10 bar
Oil type	50180751
Oil viscosity	

Trax Spring	x
Rebound disk height	4 mm
Stroke	58 mm
Shock length	311.5 mm
Bump rubber	46181171

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge	Teilenummer
Feder weicher	65-75		(59) 68-130		70189016
Feder STANDARD	75-85		(59) 72-130		70189001
Feder härter	85-95		(59) 76-130		70189003

Shims piston 1

Qty	Compression	Qty	Rebound
1	12x16x0.30	2	12x22x0.30
1	12x26x0.20	1	12x19x0.30
1	12x32x0.20	1	12x22x0.25
1	12x34x0.20	1	12x24x0.25
1	12x36x0.20	1	12x26x0.20
2	12x38x0.25	1	12x28x0.20
3	12x40x0.25	2	12x30x0.20
1	12x36x0.10	1	12x24x0.10
2	12x40x0.25	1	12x32x0.20

Piston-No.:	46810560
Piston-bleed	0 mm

Shims piston 2

Qty	Compression	Qty	Rebound

Piston-No.:	
Piston-bleed:	

Details compression unit:

Qty	Description, dimension
1	6x9.5x0.30
1	6x14x0.20
1	6x16x0.20
1	6x18x0.20
1	6x20x0.25
4	6x22x0.25

Note:

Legend:

TBD = to be defined

- = no comment

Index	Date	Name	Description of modification

Created by:	
Creation date:	

Bitte hier den Dateinamen eingeben | Templ.: MSP_Shock_Setting-list_V01 | page 1 / 1

release stamp