The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

Settingliste Federbein

PERFORMANCE SYSTEMS

Artikelnummer:	**15187N42**	**Typ:**	**4618 PDS**
Modellbezeichnung: **(ohne Jahresangabe)**	**Freeride 250**	**Druckstufen-ventil:**	**DCC 20 cpl.** 50180213S20

	Fahrer Komfort	STANDARD	*Fahrer Sport*	*volle Nutzlast*
Druckstufendämpfung Low Speed (Klicks offen bzw. Markierung)	*20*	15	*10*	
Druckstufendämpfung High Speed (Umdrehungen offen)	*2.5*	2.0	*1.0*	
Zugstufendämpfung (Klicks offen bzw. Markierung)	*20*	15	*10*	
Federvorspannung	*8 mm*	8 mm	*8 mm*	*mm*
Preload Adjuster (Umdrehungen vorsp.)				

Statischer Durchhang	15 mm
Fahrtdurchhang	80 mm
Gasdruck	10 bar
Öl Type	501800751
Öl Viskosität	SAE 2.5

Nadel	
Höhe Scheibe Zugstufe	0 mm
Hub	87 mm
Einbaulänge	367 mm
Gummipuffer	50180276

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge	Teilenummer
Feder weicher	*65-75 kg*	*N/mm*	*(61/59)55-215*	*215 mm*	*91010-0170*
Feder STANDARD	75-85 kg	N/mm	(61/59) 55/63/71-215	215 mm	9101-0324
Feder härter	*85-95 kg*	*N/mm*	*(61/59)58/62/74-215*	*215 mm*	*9101-0323*

Shims Kolben 1

Stk	Druckstufe	Stk	Zugstufe
3	Ø 12x17x0.30	1	Ø 12x19x0.30
1	Ø 12x22x0.15	1	Ø 12x28x0.20
1	Ø 12x24x0.15	1	Ø 12x30x0.20
1	Ø 12x28x0.15	1	Ø 12x22x0.10
1	Ø 12x32x0.15	1	Ø 12x32x0.20
1	Ø 12x36x0.15		
4	Ø 12x40x0.25		

Kolben Nummer	46810560
Kolben Freibohrung	0,00 mm

Shims Kolben 2

Stk	Druckstufe	Stk	Zugstufe
1	Ø 10x19x0.30	1	Ø 10x23x0.30
1	Ø 10x21x0.20	1	Ø 10x16x1.00
1	Ø 10x23x0.20	1	Ø 16x25x0.30
1	Ø 10x25x0.20		
1	Ø 10x27x0.20		
1	Ø 10x29x0.20		
1	Ø 10x31x0.20		
5	Ø 10x33x0.20		

Kolben Nummer	14460016
Kolben Freibohrung	0,00 mm

Details Druckstufenventil:

Stk.	Bezeichnung, Dimension
1	Einstellfeder 50180207
1	Shim Ø6x9x0,3
1	Shim Ø6x14x0,2
1	Shim Ø6x16x0,2
1	Shim Ø6x18x0,2
1	Shim Ø6x20x0,2
1	Shim Ø6x22x0,2
1	Shim Ø6x18x0,1
1	Shim Ø6x22x0,15

Legende:	TBD = to be defined (noch zu definieren)	- = keine Angabe

Bemerkungen:

Index	Datum	Name	Änderungsbeschreibung
#WERT!			

Name Ersteller:	M.Faelt
Datum Erstellung:	23.04.2013

Freigabefeld

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

Shock setting list

PERFORMANCE SYSTEMS

Article number:	**15187N42**	**Type:**	**4618 PDS**
Modeldescription: (without modelyeardeclaration)	**Freeride 250**	**Compression damping valve:**	**DCC 20 cpl.** 50180213S20

	Driving comfort	STANDARD	*Driving sport*	*max. payload*
Compression damping Low Speed (clicks open or marking)	*20*	15	*10*	
Compression damping High Speed (turns open)	*2.5*	2.0	*1.0*	
Rebound damping (clicks open or marking)	*20*	15	*10*	
Spring preload	*8 mm*	8 mm	*8 mm*	*mm*
Preload Adjuster (turns preload)				

Static sag	15 mm
Riding sag	80 mm
Gas pressure	10 bar
Oil type	501800751
Oil viscosity	SAE 2.5

Needle	
Rebound disk height	0 mm
Stroke	87 mm
Shock length	367 mm
Bump rubber	50180276

Spring	Riders weight	Spring rate	Spring description	Spring length	Part number
Spring softer	*65-75 kg*	*N/mm*	*(61/59)55-215*	*215 mm*	*91010-0170*
Spring STANDARD	75-85 kg	N/mm	(61/59) 55/63/71-215	215 mm	9101-0324
Spring harder	*85-95 kg*	*N/mm*	*(61/59)58/62/74-215*	*215 mm*	*9101-0323*

Shims piston 1			
Qty	Compression	Qty	Rebound
3	Ø 12x17x0.30	1	Ø 12x19x0.30
1	Ø 12x22x0.15	1	Ø 12x28x0.20
1	Ø 12x24x0.15	1	Ø 12x30x0.20
1	Ø 12x28x0.15	1	Ø 12x22x0.10
1	Ø 12x32x0.15	1	Ø 12x32x0.20
1	Ø 12x36x0.15		
4	Ø 12x40x0.25		
Piston number			46810560
Piston bleed			0 mm

Shims piston 2			
Qty	Compression	Qty	Rebound
1	Ø 10x19x0.30	1	Ø 10x23x0.30
1	Ø 10x21x0.20	1	Ø 10x16x1.00
1	Ø 10x23x0.20	1	Ø 16x25x0.30
1	Ø 10x25x0.20		
1	Ø 10x27x0.20		
1	Ø 10x29x0.20		
1	Ø 10x31x0.20		
5	Ø 10x33x0.20		
Piston number			14460016
Piston bleed			0 mm

Details compression unit:	
Qty	Description, dimension
1	Adjusting spring 50180207
1	Shim Ø6x9x0,3
1	Shim Ø6x14x0,2
1	Shim Ø6x16x0,2
1	Shim Ø6x18x0,2
1	Shim Ø6x20x0,2
1	Shim Ø6x22x0,2
1	Shim Ø6x18x0,1
1	Shim Ø6x22x0,15

Legend:	TBD = to be defined	- = no comment

Note:

Index	Date	Name	Modification description

Draftsman:	M.Faelt
Creation date:	2013-04-23

Release stamp

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.