

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterreifeintragung vorbehalten! Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

Settingliste Gabel



Artikelnummer:	14-18-1Q-26	Typ:	Semiaktiv
Modellbezeichnung: (ohne Jahresangabe)	GB.1290 ADV SAFE	Bezeichnung:	WP Semiactive

--

Sensorseite LINKS	
Ölmenge	680 ml
Öl Type Außenwerk	4860-1166
Öl Viskosität	SAE 4
Federweg	200 mm
Gabelänge	885 mm

Dämpferseite RECHTS	
Ölmenge	430 ml
Öl Type	4860-1166
Öl Viskosität	SAE 4
Federweg	200 mm
Gabellänge	885 mm

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge mit Vorspannbüchse	Teilenummer
<i>Feder weicher</i>	<i>kg</i>	<i>N/mm</i>		<i>mm</i>	
Feder STANDARD	kg	12 N/mm	438.430.00.120	443 mm	9141-0110
<i>Feder härter</i>	<i>kg</i>	<i>N/mm</i>		<i>mm</i>	

--

--

Legende:	TBD = to be defined (noch zu definieren)	- = keine Angabe
-----------------	--	------------------

Bemerkungen:
WP empfiehlt dringend die Verwendung der genau spezifizierten Öl Type.

				Name Ersteller:	Schlerpf D.
				Datum Erstellung:	07.04.2016
A	04.11.2016	D. Schlerpf	Serienfreigabe		
Index	Datum	Name	Änderungsbeschreibung		
	14-18-1Q-26_A_Serie_SL		14-18-1Q-26	Seite 1 von 1	

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration. This legend shall be included on any kind of reproduction of this document.

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmusterreife vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.



Front fork Settinglist

article number:	14-18-1Q-26	System:	Semiaktiv
Modeldescription: (without yeardeclaration)	GB.1290 ADV SAFE	Type:	WP Semiactive

--

Sensorside LEFT	
amount of oil	680 ml
oil type	4860-1166
oil viscosity	SAE 4
wheel travel	200 mm
fork length	885 mm

Dampingside RIGHT	
amount of oil	430 ml
oil type	4860-1166
oil viscosity	SAE 4
wheel travel	200 mm
fork length	885 mm

Spring	Riders weight	spring rate	Spring description	Spring length with preload spacer	Part number
<i>Feder weicher</i>	<i>kg</i>	<i>N/mm</i>		<i>mm</i>	
Feder STANDARD	kg	12 N/mm	438.430.00.120	443 mm	9141-0110
<i>Feder härter</i>	<i>kg</i>	<i>N/mm</i>		<i>mm</i>	

--

--

Legend:	TBD = to be defined	- = no comment
----------------	---------------------	----------------

Note:	WP recommends the use of the specified oil
--------------	--

				Darftzman	Schlerpf D.
				Creation Date:	07.04.2016
A	04.11.2016	D. Schlerpf	production release		
Index	Datum	Name	Modification description		
14-18-1Q-26_A_Serie_SL			14-18-1Q-26	page 1 of 1	

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration.
This legend shall be included on any kind of reproduction of this document.

Release Stamp