SETTINGLIST FORK OEM

Artikelnummer:	**14188S10**	**System:**	**SPLIT FORK**
Modellbezeichnung:(ohne Jahresangabe)	**KTM 690 End R**	**Gabeltyp:**	**XPLOR 5448**

	Fahrer Komfort	STANDARD	*Fahrer Sport*	*volle Nutzlast*
Druckstufendämpfung (Klicks offen)	*20*	15	*10*	*10*
Zugstufendämpfung (Klicks offen)	*20*	15	*10*	*10*
Preload Adjuster (im Uhrzeigersinn)	-	-	-	-

Ölmenge (Standard	640	ml
Ölmenge (min-max)	-	ml

Öl Type	48601166
Öl Viskosität	SAE 4
Federweg	250
Gabellänge	895

Feder	Gewicht Fahrer	Federrate	Feder Bezeichnung	Federlänge mit Vorspannbüchse	Teilenummer
Feder weicher	-	-	-	-	-
Feder STANDARD	75 - 85	5,9	435.430.00.59	435	91410143
Feder härter	-	-	-	-	-

Gabelbein Druckstufe (Links)

		Cartridge Art. Nr.	48600763
Stk	**Druckstufe Midvalve**	**Stk**	**Zugstufe Midvalve**
1	14.5mm Cone		
Wechselventil Hubhöhe		-	
Wechselventil Feder Art.Nr.		-	
Kolben Midvalve Art.Nr.		48601843S	
Tap Art.Nr.		-	
Nadel Art.Nr.		48601558S	
Mutter Midvalve Art.Nr.		-	
Stk	**Druckstufe Basevalve**	**Stk**	**Zugstufe Basevalve**
2	6x18x0,40	1	8x24x0,40
1	6x11x0,25		
1	6x12x0,10		
1	6x14x0,10		
1	6x16x0,10		
1	6x18x0,10		
1	6x20x0,10		
1	6x22x0,10		
1	6x24x0,10		
1	6x18x0,10		
3	6x24x0,10		
Wechselventil Hubhöhe		1,6	
Wechselventil Feder Art.Nr.		48600202	
Kolben Basevalve Art.Nr.		48601934S	
Mutter Art.Nr.		48600163	

Gabelbein Zugstufe (Rechts)

		Cartridge Art. Nr.	48600763
Stk	**Druckstufe Midvalve**	**Stk**	**Zugstufe Midvalve**
1	8x16x0,20	1	6x14x0,25
1	8x10x0,20	1	6x10x0,30
1	8x12x0,10	1	6x11x0,15
1	8x14x0,10	1	6x12x0,15
1	8x16x0,10	1	6x13x0,15
1	8x18x0,10	1	6x14x0,15
3	8x20x0,10	1	6x15x0,15
		1	6x16x0,15
		1	6x18x0,15
		1	6x14x0,10
		7	6xT20x0,10
Wechselventil Hubhöhe		0,40	
Wechselventil Feder Art.Nr.		48600382	
Kolben Midvalve Art.Nr.		48602002	
Tap Art.Nr.		48600576S	
Nadel Art.Nr.		48600277	
Mutter Midvalve Art.Nr.		40540486	
Stk	**Druckstufe Basevalve**	**Stk**	**Zugstufe Basevalve**
2	6x18x0,40	1	8x24x0,40
1	6x11x0,25		
1	6x12x0,10		
1	6x14x0,10		
1	6x16x0,10		
1	6x18x0,10		
1	6x20x0,10		
1	6x22x0,10		
4	6x24x0,10		
1	6x18x0,10		
Wechselventil Hubhöhe		1,6	
Wechselventil Feder Art.Nr.		48600202	
Kolben Basevalve Art.Nr.		48601934S	
Mutter Art.Nr.		48600163	

Bemerkung

For reference only: The fork has 110mm of Air chamber

			Ersteller:	G. Gurtner
14188S10_D_Serie_SL	Templ.: OEM_SPLIT_Fork_SL_V2.2	Seite 1/1	**Datum:**	24/07/2018

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.

SETTINGLIST FORK OEM

Article-No.:	14188S10	System:	SPLIT FORK
Model description:(without year declaration)	KTM 690 End R	Type:	XPLOR 5448

	driving comfort	STANDARD	driving sport	max.payload
Compression damping (clicks open or marking)	20	15	10	10
Rebound damping (clicks open or marking)	20	15	10	10
Preload Adjuster (clock wise)	-	-	-	-

oil capacity (standard)	640	ml
oil capacity (min-max)	-	ml

Oil type	48601166
Oil viscosity	SAE 4
Fork stroke	250
Fork length	895

Spring	Riders weight	Spring rate	Spring description	Spring length with preload spacer	Part.-No.
Spring softer	- kg	- N/mm	-	- mm	-
Spring STANDARD	75 - 85 kg	5,9 N/mm	435.430.00.59	435 mm	91410143
Spring harder	- kg	- N/mm	-	- mm	-

Fork leg compression (left side)

Cartridge Art. No.			48600763
Qty	**Compression Midvalve**	**Qty**	**Rebound Midvalve**
1	14.5mm Cone		
Check valve lift height		-	
Check valve spring Art. No.		-	
Piston Midvalve Art. No.		48601843S	
Tap art. No.		-	
Needle Art.No.		48601558S	
Nut Art. No.		-	
Qty	**Compression Basevalve**	**Qty**	**Rebound Basevalve**
2	6x18x0,40	1	8x24x0,40
1	6x11x0,25		
1	6x12x0,10		
1	6x14x0,10		
1	6x16x0,10		
1	6x18x0,10		
1	6x20x0,10		
1	6x22x0,10		
1	6x24x0,10		
1	6x18x0,10		
3	6x24x0,10		
Check valve lift height		1,6	
Check valve spring Art.No.		48600202	
Piston Basevalve Art.No.		48601934S	
Nut Basevalve Art.No.		48600163	

Fork leg rebound (right side)

Cartridge Art. No.			48600763
Qty	**Compression Midvalve**	**Qty**	**Rebound Midvalve**
1	8x16x0,20	1	6x14x0,25
1	8x10x0,20	1	6x10x0,30
1	8x12x0,10	1	6x11x0,15
1	8x14x0,10	1	6x12x0,15
1	8x16x0,10	1	6x13x0,15
1	8x18x0,10	1	6x14x0,15
3	8x20x0,10	1	6x15x0,15
		1	6x16x0,15
		1	6x18x0,15
		1	6x14x0,10
		7	6xT20x0,10
Check valve lift height		0,40	
Check valve spring Art. No.		48600382	
Piston Midvalve Art. No.		48602002	
Tap art. No.		48600576S	
Needle Art.No.		48600277	
Nut Art. No.		40540486	
Qty	**Compression Basevalve**	**Qty**	**Rebound Basevalve**
2	6x18x0,40	1	8x24x0,40
1	6x11x0,25		
1	6x12x0,10		
1	6x14x0,10		
1	6x16x0,10		
1	6x18x0,10		
1	6x20x0,10		
1	6x22x0,10		
4	6x24x0,10		
1	6x18x0,10		
Check valve lift height		1,6	
Check valve spring Art.No.		48600202	
Piston Basevalve Art.No.		48601934S	
Nut Basevalve Art.No.		48600163	

Note

For reference only: The fork has 110mm of Air chamber

			Created by:	G. Gurtner
14188S10_D_Serie_SL	Templ.: OEM_SPLIT_Fork_SL_V2.2	Page 1/1	Date:	24/07/2018

The copying, distribution and utilization of this document as well as the communication of its contents and parts of its contents to others without expressed authorization (in written form) is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of patent and utility model registration!
This legend shall be included on any kind of reproduction of this document.

Weitergabe sowie Vervielfältigung dieses Dokumentes, Verwertung und Mitteilung seines Inhaltes und Teilen davon sind verboten, soweit nicht ausdrücklich schriftlich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent- und Gebrauchsmustereintragung vorbehalten!
Dieser Text muss auf jeglicher Reproduktion dieses Dokumentes aufscheinen.